



FEATURES


- Strict selection of appearance and electric performance before encapsulation
- Excellent effect at low light level
- High transparent tempered glass
- High quality EVA and back film, anodic oxidized aluminum frame and waterproof junction box
- Unique process making panels nice-looking , rugged weather-resistant, and easy to install
- A leak hole design against seeped icing and frame distortion

QUALITY WARRANTY AND SAFETY

- 90%/12years, 80%/25years
- We have obtained the certification of ISO9001:2000(Quality Management System) and TUV, CE,UL,etc. We operate strictly according to quality management system and management procedures.

RECOMMENDED APPLICATION

- Building Integrated Photovoltaic
- Residential Rooftop System
- Tracking System
- On-Grid and Off-Grid Utility System
- On-Grid and Off-Grid Commercial System



RISUN TECHNOLOGY CO., LTD
Add: Building C, 2 Kezhi Road, Suzhou Industrial Park, 215100 China
T: 86-512-69567985 F: 86-512-69566882
sales@risun-cn.com Web: www.risun-cn.com



WWW.RISUN-CN.COM




TYPICAL PROPERTIES

	RSM72-156P	RSM72-156P	RSM72-156P	RSM72-156P	RSM72-156P
Max-Power Pm(W)	260	270	280	290	300
Max-Power Voltage-Vm(V)	44.91	45.16	45.33	45.6	45.67
Max-Power Current-Im(A)	7.42	7.65	7.87	8.08	8.29
Open-Circuit-Voc(V)	35.03	35.29	35.59	35.89	36.19
Short-Circuit-Isc(A)	8.39	8.47	8.56	8.64	8.73
Power Tolerance(%)	3%	3%	3%	3%	3%

MECHANICAL PROPERTIES

Number Type and Arrangement of Cells	72pcs polycrystalline
Cell Size	156*156mm
No of Bypass Diodes	6pcs
Max Series Fuse	15A
Pm Temperature coefficient	-0.45%/°C
ISC Temperature coefficient	0.05%/°C
VOC Temperature coefficient	-0.35%/°C
NOCT Nominal Operating Cell Temperature	47°C
Cable Type Diameter and Length	4mm 900mm
Dimension A*B*C	1950*990*50mm
No of Draining Hole in Frame	8
Glass Type and Thickness	High transmit low iron tempered glass 3.2mm



RISUN TECHNOLOGY CO., LTD

Add: Building C, 2 Kezhi Road, Suzhou Industrial Park, 215100 China

T: 86-512-69567985 F: 86-512-69566882

sales@risun-cn.com Web: www.risun-cn.com